

Cordless MULTIMASTER AMM 700 1.7 Q Autoglas

Battery-powered oscillating multi-tool

Our best oscillating cordless MultiMaster for the automotive sector including an extensive set of accessories extensive for cutting out windows and work on the car body.

Product number: 7 129 35 62 24 0



Details

- > Designed for cutting out windows and work on the car body.
- > Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- > QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- > Hexagonal tool holder for optimum torque transfer.
- > 18 V FEIN PowerDrive motor: very powerful and virtually wear-free, brushless motor offering great efficiency, ability to handle extreme loads and a long service life.
- > Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- > Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- > SafetyCell technology: perfect protection against overload, overheating and total discharge thanks to Li-ion batteries with individual cell monitoring.
- > The battery charge can be read off the battery.

Price includes

- ✓ 1 protective cover for tool changes
- ✓ 1 L-shaped cutter blade, toothed (form 209)
- ✓ 3 L-shaped cutter blades, toothed (form 207)
- ✓ 2 Li-ion battery packs (18 V / 6 Ah)
- ✓ 1 Straight cutter blade, Z-bend, toothed (form 081)
- ✓ 2 L-shaped cutter blades, toothed (form 208)
- ✓ 1 Straight cutter blade, Z-bend, with adjustable roller stop (form 143)
- ✓ 1 rapid charger ALG 80
- ✓ 1 each U-shaped cutter blade, reinforced design (forms 157 and 111)
- ✓ 2 U-shaped cutter blades, reinforced design, toothed (form 212)
- ✓ 1 sharpening stone (6 37 19 010 01 4)
- ✓ 1 plastic carrying case



Technical data

TECHNICAL DATA

Battery voltage	18 V
Battery capacity	6 Ah
Battery compatibility	Li-ion / HighPower Li-ion
Battery interface	MultiVolt
Oscillations	10,000 - 19,500 rpm
Tool Holder	Hexagon
Tool change	QuickIN
Amplitude	2 x 1,7°
Weight with battery	1.80 kg
Weight without storage battery	1.10 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Uncertainty of measured value
KpA

83 dB
3 dB

Sound power level LWA
Uncertainty of measured value
KWA

94 dB
3 dB

Sound peak value
LpCpeak
Uncertainty of measured value
KpCpeak

97 dB
3 dB

Application examples

